

JIVA-8315E

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	JIVA-8315E	JIVA-8315E-i
Processor	Intel Pentium Dual Core 2.3 GHz / 1 MB Cache CPU or Intel Core 2 Duo 2.26 ~ 2.53 GHz / 3 ~ 6 MB Cache CPU	
System Memory	DDR3 1066 MHz, SO-DIMM socket x 2, max 8 GB, default 2 GB	
Storage Device	2.5" SATA HDD or SSD Kit (Optional)	
Power Supply	12V DC power adaptor, 80W	
Audio	Line out / Mic in / 2W speaker (Optional)	
OS support	Win7 / Win XP Pro / POSReady 7 / POSReady 2009 / Linux	
Display		
LCD	15" TFT LCD, 1024 x 768 resolution	
Touch Function	Resistive, 5-wire, USB Interface	IR touch
Brightness Control	By software control	
Tilt Adjustment	From 15° to 75°	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
Parallel Port	Yes	
Serial Port	DB9 x 4, with 5V support on COM1 / COM2 / COM3 / COM4	
PS/2 Keyboard	Yes	
PS/2 Mouse	Yes	
UPS Port	Yes, battery (Optional)	
Standard USB Port	5	
VGA Port	D-SUB 15 pins, with 12V power for Posiflex LCD Monitor	
CR Port	1, control 2 CR	
Physical Dimension		
Dimension (W x D x H in mm)	376 x 321 x 372	
Weight (N. W. in kg)	10.3	
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
PD-302	2 x 20 LCD, rear top mount	
PD-305	2 x 20 LCD, rear base mount	
PD-306 / PD-306U	2 x 20 LCD, default 200 mm pole	
PD-2602 / PD-2602U	2 x 20 VFD, default 200 mm pole	
PD-76x2	240 x 64 dot Graphics LCD, 200 mm pole	
SSD	8 GB minimum	
MSR	SD-266,3 tracks and JIS-II(Optional) or Finger Print sensor(Optional) SD-876,3 tracks and JIS-II(Optional) or RFID (Optional) or WiFi (Optional)	
UPS Battery	2300 mAh / 12V	
2nd LCD Display	12" LM-6101A-B, 15" LM-8015B	
2nd HDD	Yes	
RAID Function	Support RAID 1 (Disk mirroring)	
HT-022	COM5/COM6 adaptor board ,with 5V support	
BC-100U	Barcode card reader, USB interface	
KP-100	Mini footprint design security keyboard, 40 keys (24 programmable keys and ten keys configuration) attachment, Smart card reader(Optional), MSR: 2 or 3 tracks or JIS-II (Optional)	
Certifications		

JIVA-8315E

Advanced POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2013 JIVA83Q1C1

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

JIVA-8315E

Posiflex introduces the JIVA-8315E as a high-end POS terminal.

The JIVA-8315E leads other similar products in terms of its high performance in ultra intensive operation, supported by high-end CPU, RAID 1 backup, UPS emergency power, and Resistive (Or IR) touch screen. The built-in UPS function of JIVA-8315E is embedded on main board developed by Posiflex.

JIVA-8315E supports up to Intel Core 2 Duo 2.53 GHz CPU and comprises 15" LCD, and also support versatile peripheral options such as MSR, customer pole display, programmable keypad and a wide range of connectivity to meet numerous applications.

The JIVA-8315E embodies elegant taste with higher thermal dissipation for retailers to run mass transaction easily.



Key Features

- ▶ Resistive or IR touch (Optional) screen : 15" LCD 1024 x 768 resolution
- ▶ Spill-resistant design to prevent careless spill and provide easy cleaning for a wide range of applications
- ▶ Supports up to Intel Core 2 Duo 2.53 GHz CPU (Optional)
- ▶ Memory DDR3 inside
- ▶ RAID 1 (Disk Mirroring) support to backup important data (Optional)
- ▶ UPS (Embedded on board developed by Posiflex) support to avoid sudden power loss
- ▶ Cable cover with lock to protect rear I/O from unauthorized access
- ▶ Patented finger lever "Gear Lock" to adjust the LCD tilt angle from 15° to 70°
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Base bottom cable guide design for safety and neat outlook
- ▶ Generation 6 super slim base stand (Optional)

